

DECLARATION OF PERFORMANCE

No.: 001-1-CPR-2013

METEON® FR

1	Unique identification code of the product-type	METEON® FR
2	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	METEON® FR batch numbers on panel label
3	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Compact laminate panels for external wall and ceiling finishes Type EDF according to EN438 part 6
4	Name , registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	TRESPA International B.V. Wetering 20 NL – 6002 SM Weert
5	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	-
6	System or systems of AVCP (=assessment and verification of constancy of performance) of the construction product as set out in Annex V of CPR	System 1
7	Name and identification number of the notified body in case of DoP concerning a construction product covered by a harmonized standard	Notified product certification body 0958 issued a certificate of constancy of performance based on - determination of product type based on type testing - initial inspection of manufacturing plant and factory production control - continuous surveillance, assessment and evaluation of factory production control

DECLARATION OF PERFORMANCE

No.: 001-1-CPR-2013

8	Declared performance		
Essential characteristics	Performance	Harmonized technical specification	
Reaction to fire	≥ 6 mm B-s2,d0 ≥ 8 mm (Metal Frame) B-s1,d0	EN 438 - 7	
Fire Resistance	NPD		
Water vapour permeability	NPD		
Resistance to fixings	6 mm ≥ 2.000 N 8 mm ≥ 3.000 N ≥ 10 mm ≥ 4.000 N		
Direct airborne sound insulation	NPD		
Flexural tensile strength	≥ 120 MPa		
Flexural modulus of elasticity	≥ 9000 MPa		
Thermal resistance / conductivity	NPD		
Release of formaldehyde	E1		
Sound absorption	NPD		
Thermal shock resistance	pass		
Durability: Resistance to wet conditions	pass		
Durability: Density	$\geq 1,35$ g/m ³		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Weert, 01.07.2013

.....
Paul Booms (COO)

.....
Christine Klomp (Product compliance officer)